Features:

- State of the art design: sleek, compact and stylish outlook
- Superb energy efficiency
- Available in 2 colour variations: mat crystal white and mat crystal silver
- Newly designed air distribution flap prevents draft feeling by activating the 'comfort mode'
- The new titanium apatite photocatalytic air purification filter increases the active surface area for effective purification and deodorisation
- Horizontal and vertical auto-swing + 3D-air flow ensure efficient air and temperature distribution.
- Powerful mode can be selected for rapid cooling or heating
- The movement sensor saves power consumption in unoccupied rooms
- Indoor unit silent operation: "Silent" button on the remote control lowers the operation sound of the indoor unit by 3dB(A).

Benefits:

24 hour timer

Timer can be set to start cooling/heating anytime during a 24-hours period.

Auto cooling-heating changeover

Automatically selects cooling or heating mode to achieve the set temperature (heat pump types only).

Auto fan speed

Automatically selects the necessary fan speed to reach or maintain the set temperature.

Auto-restart

The unit restarts automatically at the original settings after power failure.

Centralised control

Centralised control to start, stop and regulate several air conditioners from one central point.

((optional))

Comfort mode

The flap changes the discharge angle horizontally for cooling operation and downward vertically for heating operation. This in order to prevent cold or warm air from blowing directly on the body.

Dry programme

Allows humidity levels to be reduced without variations in room temperature.

Energy efficiency

Daikin air conditioners are energy efficient and economical.

Fan speed steps

Allows to select up to the given number of fan speed.

((5 steps))

Horizontal auto swing

Possibility to select automatic horizontal moving of the air discharge louvre, for uniform air flow and temperature distribution.

Indoor unit silent operation

Lowers the operation sound of the indoor unit by 3dB(A). This function is useful when studying or sleeping.

Infrared remote control

Infrared remote control with LCD to start, stop and regulate the air conditioner from a distance.

((standard))

Movement sensor

The sensor detects whether someone is in the room. When the room is empty, the unit switches to economy mode after 20 minutes and restarts when a person enters the room.

Night set mode

Saves energy, by preventing overcooling or overheating during night time.

Powerful mode

If the room temperature is too high/low, it can be cooled down/heated quickly by selecting the 'powerful mode'. After the powerful mode is turned off, the unit returns to the preset mode.

Self-diagnosis

Simplifies maintenance by indicating system faults or operating anomalies.

Titanium apatite photocatalytic air purification filter

Removes airborne dust particles, decomposes odours and restrains the reproduction of bacteria, viruses, microbes, this to ensure a steady supply of clean air.

((integrated titanium apatite))

Vertical auto swing

Possibility to select automatic vertical moving of the air discharge louvre, for uniform air flow and temperature distribution.

Whisper quiet

Daikin indoor units are whisper quiet. Also the outdoor units are guaranteed not to disturb the quiet of the neighbourhood.

Technical data:

					FTXG25CVMBW	FTXG35CVMBW	FTXG25CVMBS
Casing	Colour				Mat Crystal White	Mat Crystal White	Mat Crystal Silver
Dimensions	Unit	Height		mm	275	275	275
		Width		mm	840	840	840
		Depth		mm	150	150	150
Fan	Air Flow Rate	Cooling	High	m³/min	7.40	7.90	7.40
			Medium	m³/min	6.00	6.30	6.00
			Low	m³/min	4.40	4.70	4.40
			Silent Operation	m³/min	3.70	4.10	3.70
		Heating	High	m³/min	7.70	7.90	7.70
			Medium	m³/min	6.90	7.10	6.90
			Low	m³/min	6.00	6.00	6.00
			Silent Operation	m³/min	5.00	5.10	5.00
Sound Level	Cooling	Sound Power	High	dBA	56.0	57.0	56.0
		Sound Pressure	High	dBA	38.0	39.0	38.0
			Medium	dBA	32.0	33.0	32.0
			Low	dBA	25.0	26.0	25.0
			Silent Operation	dBA	22.0	23.0	22.0
	Heating	Sound Pressure	High	dBA	38.0	39.0	38.0
			Medium	dBA	33.0	34.0	33.0
			Low	dBA	28.0	29.0	28.0
			Silent Operation	dBA	25.0	26.0	25.0
Refrigerant	Type				R-410A	R-410A	R-410A
Power Supply	Phase				1	1	1
	Frequency			Hz	50/60	50/60	50/60
	Voltage			V	220-240/220-230	220-240/220-230	220-240/220-230

Technical data:

					FTXG35CVMBS
Casing	Colour				Mat Crystal Silver
Dimensions	Unit	Height		mm	275
		Width		mm	840
		Depth		mm	150
Fan	Air Flow Rate	Cooling	High	m³/min	7.90
			Medium	m³/min	6.30
			Low	m³/min	4.70
			Silent Operation	m³/min	4.10
		Heating	High	m³/min	7.90
			Medium	m³/min	7.10
			Low	m³/min	6.00
			Silent Operation	m³/min	5.10
Sound Level	Cooling	Sound Power	High	dBA	57.0
		Sound Pressure	High	dBA	39.0
			Medium	dBA	33.0
			Low	dBA	26.0
			Silent Operation	dBA	23.0
	Heating	Sound Pressure	High	dBA	39.0
			Medium	dBA	34.0
			Low	dBA	29.0
			Silent Operation	dBA	26.0
Refrigerant	Type				R-410A
Power Supply	Phase				1
	Frequency			Hz	50/60
	Voltage			V	220-240/220-230

Specifications are subject to change without any prior notice.